



MANUFACTURER: EMERGENCY TEL. NUMBERS:

Koel Colours Private Limited. F-11, Nand-Jyot Industrial Premises, Andheri-Kurla Road, Safed Pool,

Sakinaka, Andheri (East), Mumbai – 400 072. sales@koelcolours.com +91-22-67723456 +91-22-6676 4531/32 +91-22-2850 0754

#### **SECTION 1: PRODUCT INFORMATION**

PRODUCT NAME: TartrazineCOLOUR INDEX NO: 19140PRODUCT CODE: Koelor - 180CHEMICAL FAMILY : Pyrazolone

**COMPONENT (s)** : FD & C Yellow 5

**HAZARDOUS** : No **C.A.S. No.** : 1934-21-0

#### **SECTION 2: HAZARDS IDENTIFICATION**

This product is not considered to be a hazardous substance as defined under OSHA's Hazard Communication Standard (29 CFR 1910.1200).

Arsenic Less than 3.0 ppm Lead Less than 2.0 ppm Mercury Less than 1.0 ppm

These levels are "Typical" quantities and may change slightly with different lots. The term "Less than" indicates that the substance was detected, but the amount was less than the quantifiable limit.

#### **SECTION 3: PHYSICAL AND CHEMICAL PROPERTIES**

Boiling Point Not applicable
Vapour Pressure Not applicable
Vapour Density Not applicable

Percent Volatile By Weight NIL Evaporation Rate NIL

Appearance and odour Orange powder. No odour

Molecular Formula C<sub>16</sub>H<sub>9</sub>N<sub>4</sub>O<sub>9</sub>S<sub>2</sub>N<sub>a3</sub>

# **SECTION 4: HEALTH HAZARD DATA**

THRESHOLD LIMIT VALUE Inert or nuisance dust

(ACGIH), 5mg/m<sup>3</sup>Respirable (ACGIH), 10 mg/m<sup>3</sup>Total dust

ISSUE		REVISION		DOCUMENT NO	NEXT REVIEW
NO.: 01	DATE: 01.06.2006	NO.: 05	DATE: 01.06.2014	KCPL(KOELOR)/MSDS/0012	DATE: 31.05.2017





CAR (OSHA), 15 mg/m<sup>3</sup> Total dust

CARCINOGENICITY This product is not considered a

carcinogen by IARC, NTP, ACGIH or OSHA

PRIMARY ENTRY ROUTE (S) Inhalation, Ingestion, Skin and Eye

Irritation

ACCUTE EFFECTS Cause mechanical skin and eye irritation

SUMMARY OF RISKS May cause mechanical skin and eye

irritation. Repeated and prolonged exposures to dust may cause a benigh

pneumoconiosis called dieresis.

CHRONIC EFFECT (S) Prolonged inhalation of dust is known as

Siderosis. On X-rays it appears to be a benigh pneumoconiosis and is not associated with pulmonary fibrosis or disability unless there is concurrent exposure to other fibrosis producing

materials.

**SECTION 5: FIRST AID MEASURES:-**

EYE CONTACT Flush eyes with generous amounts of water for at least

15 minutes. Call a physician if irritation persists.

SKIN CONTACT Wash skin with mild soap and water. Remove severely

contaminated clothing and clean before reuse. Seek medical attention in the unlikely event that irritation

occurs

INHALATION Remove to fresh air. Get medical attention if breathing

is difficult.

INGESTION If conscious, give large quantities of water to induce

vomiting. Get medical attention

EFFECTS OF OVEREXPOSURE May cause mechanical irritation to eyes and respiratory

tract

**EMERGENCY AND FIRST AID** 

PROCEDURES

Wash dust from skin with soap and water. Flush out eyes with large amounts of water for at least 15

minutes. See a physician

ISSUE		REVISION		DOCUMENT NO	NEXT REVIEW
NO.: 01	DATE: 01.06.2006	NO.: 05	DATE: 01.06.2014	KCPL(KOELOR)/MSDS/0012	DATE: 31.05.2017





# **SECTION 6: FIRE FIGHTING MEASURES**

Nonflammable pigment product.

Extinguishing Media Carbon dioxide, dry chemical or foam

recommended. Apply water spray to cool

exposed closed containers.

This product will not burn.

Special Fire Fighting Procedures Self-contained breathing apparatus and

full protective equipment recommended

**Unusual Fire and Explosion Hazards** 

**FLAMMABILITY DATA** 

Flash Point

Non-flammable material

Flammability Limits

Auto ignition Temperature

Dust Cloud Ignition Temperature

Dust Layer Ignition Temperature

Not applicable

Not applicable

# **SECTION 7: SPILL OR LEAK PROCEDURES**

# Steps to take in case material is released or spilled

Normal clean-up procedures. Care should be taken to avoid causing dust to become airborne. Vacuum cleaning systems are recommended.

# **SECTION 8: SPECIAL PROTECTION INFORMATION**

Eye Protection Safety glasses, goggles, face shield.

Skin Protection Leather or rubber gloves.

Respiratory Protection Use of a NIOSH approved dust respirator is

recommended when exposure limits may

be exceeded.

Ventilation Exhaust ventilation to collector or

containment recommended controlling

dust below exposure limits.

# **SECTION 9: HANDLING AND STORAGE**

ISSUE		REVISION		DOCUMENT NO	NEXT REVIEW
NO.: 01	DATE: 01.06.2006	NO.: 05	DATE: 01.06.2014	KCPL(KOELOR)/MSDS/0012	DATE: 31.05.2017





#### Handling:

Good industrial hygiene requires that employee exposure be maintained below the recommended TLV. This is preferably achieved through the provision of adequate ventilation where necessary. Personal respiratory protection should be employed where dust cannot be controlled in this way.

## Storage:

Store in a moderately cool, dry, well-ventilated area away from direct sources of heat. Empty containers may contain product residues and should be handled appropriately. Position containers such that any labeling information is visible.

#### **SECTION 10: STABILITY AND REACTIVITY**

#### **GENERAL**

This product is a stable compound and hazardous polymerization will not occur.

#### **INCOMPATIBILITY**

None known. Avoid contact with reactive material.

## **SECTION 11: TOXICOLOGICAL INFORMATION**

There are no known dangerous acute or chronic effects associated with the use of this material.

#### **SECTION 12: ECOLOGICAL INFORMATION**

This product has not been evaluated for its ecotoxicity. However, the biodegradation of colorants under aerobic conditions is expected to be poor and there is no evidence to suggest they create any significant ecological problems when released into the environment. Since These pigments are mostly soluble compounds, they are believed to have bioaccumulation and bioavailability characteristics.

# **SECTION 13: DISPOSAL CONSIDERATIONS**

ISSUE		REVISION		DOCUMENT NO	NEXT REVIEW
NO.: 01	DATE: 01.06.2006	NO.: 05	DATE: 01.06.2014	KCPL(KOELOR)/MSDS/0012	DATE: 31.05.2017





#### General

This product must be disposed off in accordance with all applicable federal, state and local regulations.

#### **Waste Management**

Incineration or land filling is recommended disposal techniques. Contact the state or local environmental agency for specific rules.

This product is not identified as a RCRA hazardous, WASTE UNDER 40 CFR 261, and is not regulated under CERCLA (Superfund).

# **SECTION 14: TRANSPORT INFORMATION**

Water soluble pigments are considered to be non hazardous according to U.S. department of transportation and International shipping Regulations.

# SECTION 15: USERS RESPONSIBILITY/ DISCLAIMER OF LIABILITY:-

The information set forth herein is in accordance with our present experience and knowledge, and is intended to describe the product solely with respect to health, safety and environment. Since we have no influence on the way in which our products are treated and used, we can not take any responsibility in this respect. The user must assume responsibility himself and must determine the suitability of the product for his application. All existing proprietary rights, laws and regulations shall be observed. As such, it must not be interpreted as a Guarantee of any specific property of the product.

#### **SECTION 16: OTHER INFORMATION**

For more information contact to Product Safety at

#### **Koel Colours Private Limited.**

F-11, Nand-Jyot Industrial Premises, Andheri-Kurla Road, Safed Pool, Sakinaka, Andheri (East), Mumbai – 400 072.

ISSUE		REVISION		DOCUMENT NO	NEXT REVIEW
NO.: 01	DATE: 01.06.2006	NO.: 05	DATE: 01.06.2014	KCPL(KOELOR)/MSDS/0012	DATE: 31.05.2017